Universal sliding sash window



Guidelines for completing the Universal sliding sash windows order form.

Header Details

QUOTE REQUEST - please tick this box if you are enquiring about prices only - LEAVE BLANK FOR ORDERS

Your Details - please provide us with complete and accurate information to allow rapid order processing - including full delivery address, especially if different from your office/factory address. Request the date your windows are required (standard lead time is 2-3 weeks) we will confirm delivery date by fax. Include your contact details (placed by name) in case we need to clarify anything on your order. Please give your orders a clear 'order reference' - preferably with your purchase order no. for maximum traceability and quick easy invoicing.

WINDOW DETAILS

NB: PLEASE ORDER WINDOWS IN SAME ROOM/ELEVATION TOGETHER TO HELP US MATCH SPECIFICATION/STYLE SOME WINDOWS MAY REQUIRE LARGE/LARGE SASH COMBINATION DUE TO SIZE - STANDARD IS LARGE/SMALL SASHES

Outerframe Depth - The Universal sash window is only available in one frame depth of 128mm front to back dimension.

- Window Colour White is standard, there is a Universal range of colours available please note required foiled/painted finish under OTHER.
- 2 Deep Bottom Rail A mechanically jointed aesthetic optional extra to replicate traditional sight lines - bottom sash base rail is 90mm in height.
- 3 Cill Size Universal VS have integral cills as a base to the frame, 150mm/Flush is Standard but 210mm/Projecting is available.
- 4 Hardware Standard Universal sash windows are manufactured with a full suite of matching white window hardware, we also have available hardware suites finished in gold or chrome. Other finishes are available on request subject to extended lead times and/or surcharge, please specify.
- 5 Key Locking For extra security key locking cams are fitted as standard - thumb turn/non-locking cams are available, tick 'no'.
- 6 Number of Windows If you wish to order multiple windows of identical size and specification please state required quantity here.
- Reference This offers the opportunity to reference your windows individually for easy identification on site (Lounge, bedroom, etc.) and will be displayed on frame labels.
- 8 Total Width Please state the total overall finished window width including any extras or frame extenders, etc.
- 9 Total Height Please state the total overall finished window height including any cills, extras or frame extenders, etc.
- Transom Drop Please state the dimension from the top of the outerframe to the central meeting point of the sashes, if left blank's standard is half the height of the window - but we can cater for most requirements (1/3rd - 2/3rds or 2/5ths - 3/5ths etc.).
- 11 Fire Escape? If the window needs to meet Part B fire egress requirements let us know! Please note minimum sizes do apply (will confirm compliance) and where this option is selected hardware configuration should be checked with local planning department. UK have special side hinged Fire Egress windows available (at an extra charge) to allow smaller frames to comply with Building Regulations.
- 12 Opening Restrictors Primarily a child safety feature these limit the sash opening - available in white, gold or chrome only.

- 13 Decorative Horns Aesthetic optional extras available to mimic authentic features - fitted to the bottom of the top sash, 'plant on' only.
- 14 Tilt Facility 'NO' = Standard sashes will slide up and down only, 'YES' = optional 'easy clean' tilt facility available to facilitate cleaning from inside + extra ventilation, etc. - tilt restrictor arms are fitted to all tilting sashes, 'F' = a totally fixed window (both sashes).
- 15 Vent Required 2200mm and 4400mm E/A controllable night vents are available - fitted through the head of the top sash.
- 16 Spacer Bar Colour VS are supplied with silver spacer bars as standard, gold in woodgrain, other colours are available on request. Warmedge/Thermal spacer bars are only available in white, black or grey.
- 17 W.E.R. Rating Select the BFRC approved window energy rating required. All frames with standard 4-16-4 glass configuration will be supplied 'C' rated as standard. 'A' rating not available with deep bottom rail.
- 18 Georgian Bar type Select Georgian Bar type if required, Authentic = 'A' for face planted PVCu astragal bars (inside + outside unit), Glazed In = 'Gin' for glazed in Georgian bars (inside unit only), None = 'N/A'. Please sketch Georgian layouts in the diagrams provided.
- 19 Georgian Bar Width Universal VS have two widths of Authentic Bar (22mm & 30mm) and two widths of Glazed In Bar (18mm or 25mm) please specify if you would prefer the 'SLIM' or 'WIDE' bars after specifying which type of bar is required in the field above. Wide authentic bars are only available in plain white or oak finishes.
- 20 Outside Sketch All VS are fully glazed with 4-16-4 clear 'K' Glass as standard, for any additional glazing requirements e.g. Toughened/Laminated mark the window drawings with 'T' or 'L' as applicable, for Obscure glass 'O' please confirm desired pattern.
- 21 Coupler A 2mm PVCu 'H' section trim is available for fixing multiple frames together, they also require screw fixing. As standard Universal coupled sash windows will be supplied on a continuous integral cill, for larger windows sashes will be removed for delivery/installation.
- 22 Frame Extension a small (20mm tall x 70mm deep) or large (50mm tall x 70mm deep) add-on is available if required, an odd leg adaptor (10mm tall x 19mm deep) is also available - ideal for check reveals.
- 23 Bay Assembly A non-structural variable angle bay pole is available for bays between 120° and 150° - a 90° fixed bay pole is also available.
- 24 Fixing Lugs To assist with quick, easy, high quality installation stainless steel fixing lugs are available, 'yes' = 6 supplied per window.

Additional Requirements:

Please include details of any special requirements in space provided or on supplementary sheets, e.g. drawings of bays, etc. If your sash window needs to comply with any special regulations, i.e. B.B.A. or BS7950 or if you wish for a particular W.E.R. rating please let us know, we will try to oblige. If you are planning to install sash windows in a severe weather facing location, please contact the sales office for advice.

BAYS, WELDED CILS AND ARCHED WINDOWS

A separate order form is available for arched windows, please enquire please also sketch any bay layouts on additional sheets.

NB: PLEASE GIVE FINISHED INTERNAL FACET SIZES AND REQUIRED ANGLES FOR ANY BAY WINDOW ASSEMBLIES.

Universal sliding sash window



☐ PLEASE TICK HERE IF	QUOTE REQUEST ONLY		Tel: 01/43 44 Fax: 01743 44		d Enterprise Park
Company			www.utfl.		Shrewsbury opshire SY1 3EH
Delivery Address					,
			WINDOW SPECIFIC	CATION	
			Window colour	white (standard)	
			[other (enecify)	
Postcode			L		
Reference			Deep bottom rail	no (standard)	∟ yes
Requested Delivery Date			Cill size	150mm (standard)	☐ 210mm
Telephone			HARDWARE		
Fax			White (standard) Gold Chrome		
Email			Other (specify)		
Ordered by			Key locking?	yes (standard)	no
	ly with all relevant planning requir	I ements, Building Regulations	and FENSA guidelines, etc.	- If in doubt please contact tl	he sales office for advice.
		:	:	:	:
NO. OF WINDOWS					
REFERENCE					
TOTAL VISIOUT	mm	mm	mm	mm	mm
TOTAL HEIGHT TRANSOM DROP	mm	mm	mm	mm	mm
FIRE ESCAPE?	☐YES ☐ NO	☐YES ☐ NO	☐YES ☐ NO	☐YES ☐ NO	YES □ NO
OPENING RESTRICTOR	☐ YES ☐ NO	☐ YES ☐ NO	☐YES ☐ NO	☐ YES ☐ NO	☐ YES ☐ NO
DECORATIVE HORNS	☐ YES ☐ NO	☐ YES ☐ NO	☐YES ☐ NO	☐ YES ☐ NO	☐ YES ☐ NO
TILT FACILITY	☐YES ☐NO ☐ F	☐YES ☐ NO ☐ F	☐YES ☐ NO ☐ F	☐YES ☐ NO ☐ F	☐YES ☐ NO ☐ F
VENT REQUIRED	☐YES ☐NO	☐YES ☐ NO	☐YES ☐ NO	□YES □NO	☐YES ☐ NO
SPACER BAR COLOUR					
W.E.R. RATING	□ 'A' □ 'B' □ 'C'	☐ 'A' ☐ 'B' ☐ 'C'	☐ 'A' ☐ 'B' ☐ 'C'	☐ 'A' ☐ 'B' ☐ 'C'	☐ 'A' ☐ 'B' ☐ 'C'
GEORGIAN BAR TYPE	□ A □ GIN □ NA	□ A □ GIN □ NA	☐ A ☐ GIN ☐ NA	☐ A ☐ GIN ☐ NA	□ A □ GIN □ NA
GEORGIAN BAR WIDTH	☐ SLIM ☐ WIDE	☐ SLIM ☐ WIDE	☐ SLIM ☐ WIDE	☐ SLIM ☐ WIDE	☐ SLIM ☐ WIDE
WINDOW DESIGN Please sketch in any Georgian bar or glass requirements T = Toughened glass L = Laminated O = Obscure (Please provide pattern) OBSCURE PATTERN					
COUPLER	mm	mm	mm	mm	mm
FRAME EXTENSION	@ mm		@ mm		
BAY POLE	90 VARIABLE	☐ 90 ☐ VARIABLE	☐ 90 ☐ VARIABLE	☐ 90 ☐ VARIABLE	□ 90 □ VARIABLE
FIXING LUGS	E YES □ NO	☐ YES ☐ NO	☐ YES ☐ NO	YES NO	☐ YES ☐ NO

ADDITIONAL REQUIREMENTS?